# 2025 CAN-AM MAVERICK X3 MAX X RS TURBO RR

## WITH SMART-SHOX



#### PACKAGE HIGHLIGHTS

- 200 hp. turbo charged Rotax® powerplant with intercooler
- 72.7 in. wide with over 55cm of suspension travel
- Seating for 4 people
- · Smart-Lok\* front differential
- Smart-Shox\*\* Technology featuring DDA Valve
- FOX<sup>†</sup> 2.5/3.0 PODIUM<sup>†</sup> shocks with bypass
- · Belt monitoring system
- · 850 W magneto
- 7.6 in. digital display with keypad
- X-package graphics/seats
- · 4-point harnesses with shoulder pads
- · Can-Am LED signature lights
- 14 in, aluminium beadlock wheels
- 32 in. XPS Trac Force tyres
- Full roof
- · HMWPE full skid plate

### Fiery Red & Hyper Silver

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/ 4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar 22 in. (55.9 cm) suspension travel Trophy Truck-inspired arms
Front Shocks	FOX¹ 2.5 PODIUM¹ Piggyback with bypass and Smart-Shox** technology featuring DDA valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing Arm X (TTX) with sway bar 22 in. (55.9 cm) suspension travel
Rear Shocks	FOX¹ 3.0 PODIUM¹ remote reservoir with bypass and Smart-Shox** technology featuring DDA valve (Dynamic Damping Adjustment)
TYRES & WHEELS	
Front Tyres	XPS Trac Force 32 x 10 x 15 in.
Rear Tyres	XPS Trac Force 32 x 10 x 15 in.
Wheels	15 in. cast-aluminium beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston callipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston callipers

#### **DIMENSIONS & CAPACITIES**

Estimated Dry Weight	1,942 lb (880.9 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L)
Fuel Capacity	10.5 gal (40 L)
Person Capacity	4
FEATURES	
Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10-A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights LED signature lights LED tail lights
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter-doors Full hard roof 4-point harnesses with shoulder pads HMWPE full skid plate Rear tow hook
WARRANTY	
Factory Warranty	3-year unlimited km powertrain & Rotax® engine warranty and 1-year warranty & unlimited km on the rest of the unit





